

CNC Angular Approach Cylindrical Grinder

The FANUC high performance control has been developed exclusively for the cnc angular approach cylindrical grinding industry. The canned cycles and the custom Macro B package featured in the control give the machine the versatility and speed demanded to accomplish the grinding needs of the industry.

With the marriage of the FANUC control and the ECOTECH GRINDER, we have developed a state-of-the-art CNC Angular Approach Cylindrical Grinder with the simplicity of programming today's most complex parts.



Series	Max. O.D.	Lengths Between Centers	Max Workload	Wheel Size (DxWxI.D.)	Wheelhead Hp.	Machine Weight
MK1620	8.00"	20.0" – 120.0"	400 lbs	16x2x8 inch	7.5 hp	7,059 lbs
MK1632	12.00"	30.0 "– 120.0"	400 lbs	24x3x12 inch	15 hp	9,927 lbs
MK1640	15.70"	40.0 "– 120.0"	1,100 lbs	24x3x12 inch	15 hp	32,320 lbs
MK1650	20.00"	40.0 "– 160.0"	2,205 lbs	30x3x12 inch	20 hp	38,870 lbs
MK1663	25.00"	40.0 "– 160.0"	6,608 lbs	30x3x12 inch	15.00	45,255 lbs
MK1680	32.00"	40.0 "– 160.0"	6,608 lbs	30x3x12 inch	15.00	51,400 lbs